

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims:

Claims 1- 29. (Canceled)

Claim 30. (Not entered)

Claim 31. (Currently amended) A system for monitoring changes in a skin wound over time, the system comprising:

a wound dressing including a two-dimensional array of test electrodes for application to the surface of the wound,

a circuit means electrically coupled to the two-dimensional array of test electrodes, the circuit for measuring an electrical characteristic of tissue underlying each test electrode, said circuit comprising:

a switching device for selecting successive test electrodes, and

an analyser for passing an electrical alternating current between each selected test electrode and at least one further electrode applied to the skin at a location away from the wound,

said analyser further calculating the electrical characteristic of the tissue under each currently selected test electrode as a function of the voltage difference between the currently selected test electrode and at least one reference electrode, adjacent to the currently selected test electrode; and

a display device means electrically coupled to the analyser, the display device for presenting a visual map generated using analyser circuitry of said analyser, the map indicating the size and shape of the wound based upon the measured electrical characteristic.

Claim 32. (Canceled)

Claim 33. (Canceled)

Claim 34. (Previously presented) A system as claimed in claim 31, wherein the array of test electrodes is arranged on a flexible backing of insulating material.

Claim 35. (Previously presented) A system as claimed in claim 34, wherein the array of electrodes is a rectangular array.

Claim 36. (Previously presented) A system as claimed in claim 34, wherein each test electrode is covered with a conductive gel, the resistance between adjacent test electrodes being high relative to the resistance via the gel between each test electrode and the underlying tissue.

Claim 37. (Previously presented) A system as claimed in claim 36, wherein the gel is a hydrogel.

Claim 38. (Previously presented) A system as claimed in claim 34, wherein leads for the test electrodes are also disposed on the flexible backing of insulating material and covered with an insulating material.

Claim 39. (Previously presented) A system as claimed in claim 31, wherein the two-dimensional array comprises at least 25 test electrodes.

Claim 40. (Previously presented) A system as claimed in claim 31, wherein the electrical characteristic is an impedance of the tissue underlying each test electrode.

Claim 41. (Canceled)

Claim 42. (Canceled)

Claim 43. (Canceled)

Claim 44. (Canceled)

Claim 45. (Canceled)

Claim 46. (Currently amended) A system as claimed in claim 41, wherein the further ~~said at least one other~~ electrode is also disposed on the flexible backing of insulating material.

Claim 47. (Previously presented) A system as claimed in claim 41, wherein for each test electrode a measurement is made at a plurality of different frequencies.

Claim 48. (Currently amended) A system as claimed in claim 41, wherein ~~the~~ for each measurement is made at a frequency of from 1 milliHz to 100 kHz.

Claim 49. (Canceled)

Claim 50. (Currently amended) A method of monitoring changes in a skin wound over time, the method comprising:

applying a dressing to the wound, the dressing including a two-dimensional array of test electrodes applied to the surface of the wound;[[.]]

measuring an electrical characteristic of tissue underlying each test electrode by selecting successive test electrodes, passing an electrical alternating current between each selected test electrode and a further electrode applied to the skin at a location away from the wound, and calculating the electrical characteristic of the tissue under each currently selected test electrode as a function of the voltage difference between the currently selected test electrode and at least one reference electrode adjacent to the currently selected test electrode; at various times; and

presenting a visual map indicating the size and shape of the wound based upon the measured electrical characteristic.

Claim 51. (Canceled)

Claim 52. (Canceled)

Claim 53. (Previously presented) A method as claimed in claim 50, wherein the array of test electrodes is arranged on a flexible backing of insulating material.

Claim 54. (Previously presented) A method as claimed in claim 53, wherein each test electrode is covered with a conductive gel, the resistance between adjacent test electrodes being high relative to the resistance via the gel between each test electrode and the underlying tissue.

Claim 55. (Previously presented) A method as claimed in claim 50, wherein the two-dimensional array comprises at least 25 test electrodes.

Claim 56. (Previously presented) A method as claimed in claim 50, wherein the electrical characteristic is the impedance of the tissue underlying each test electrode.

Claim 57. (Canceled)

Claim 58. (Canceled)

Claim 59. (Previously presented) A method as claimed in claim 57, wherein for each test electrode a measurement is made at a plurality of different frequencies.

Claim 60. (Canceled)

Claim 61. (Canceled)

Claim 62. (New) A system as claimed in claim 31, wherein said switching device for selecting successive test electrodes also selects, for the currently selected test electrode, at least one test electrode, adjacent to the currently selected test electrode to act temporarily as said reference electrode with respect to the currently selected test electrode.

Claim 63. (New) A system as claimed in claim 34, wherein said at least one reference electrode is a dedicated electrode on the flexible backing of insulating material.

Claim 64. (New) A method as claimed in claim 50, comprising, for each currently selected test electrode, selecting at least one test electrode adjacent to said currently selected test electrode to act temporarily as said reference electrode with respect to the currently selected test electrode.

Claim 65. (New) A system as claimed in claim 53, wherein said at least one reference electrode is a dedicated electrode on the flexible backing of insulating material.